

**Type : LT1028B-D****Characters:**


Epoxy Lens Color: Water Clear.Frosted.

**Color:** Red. Green. Blue. Amber. White.**Dia & Length:** **Base:**

T10\*28mm. BA9S

**Bulb Shape :** **For:**

Dome Indicator. Auto. Radio. Signal.

**Part Number and Description**

Part Number	Diameter Length	Color	Volts	Base	Design Current (mA)	Wave length(nm)	Lumens (M.c.d)	Life time(h)	Viewing Angle
LT1028B-RD-01D	T10*28mm	Red	DC 6V	BA9S	19±2mA	620 - 630	0.7lm	30K (h)	45°
LT1028B-RD-02D	T10*28mm	Red	DC 12V	BA9S	19±2mA	620 - 630	0.7lm	30K (h)	45°
LT1028B-RD-03D	T10*28mm	Red	DC 24V	BA9S	18±2mA	620 - 630	0.7lm	30K (h)	45°
LT1028B-RD-04D	T10*28mm	Red	DC 28V	BA9S	19±2mA	620 - 630	0.7lm	30K (h)	45°
LT1028B-RD-05D	T10*28mm	Red	DC 36V	BA9S	18±2mA	620 - 630	0.7lm	30K (h)	45°
LT1028B-RD-06D	T10*28mm	Red	DC 48V	BA9S	16±2mA	620 - 630	0.6lm	30K (h)	45°
LT1028B-RD-07D	T10*28mm	Red	DC 60V	BA9S	12±2mA	620 - 630	0.4lm	30K (h)	45°
LT1028B-RD-08A	T10*28mm	Red	AC110V	BA9S	6±2mA	620 - 630	0.2lm	30K (h)	45°
LT1028B-RD-09A	T10*28mm	Red	AC220V	BA9S	4±2mA	620 - 630	0.1lm	30K (h)	45°
LT1028B-GD-01D	T10*28mm	Green	DC 6V	BA9S	18±2mA	515 - 525	1.5lm	30K (h)	45°
LT1028B-GD-02D	T10*28mm	Green	DC 12V	BA9S	18±2mA	515 - 525	1.5lm	30K (h)	45°
LT1028B-GD-03D	T10*28mm	Green	DC 24V	BA9S	18±2mA	515 - 525	1.5lm	30K (h)	45°
LT1028B-GD-04D	T10*28mm	Green	DC 28V	BA9S	19±2mA	515 - 525	1.5lm	30K (h)	45°
LT1028B-GD-05D	T10*28mm	Green	DC 36V	BA9S	18±2mA	515 - 525	1.5lm	30K (h)	45°
LT1028B-GD-06D	T10*28mm	Green	DC 48V	BA9S	16±2mA	515 - 525	1.3lm	30K (h)	45°
LT1028B-GD-07D	T10*28mm	Green	DC 60V	BA9S	11±2mA	515 - 525	1.1lm	30K (h)	45°
LT1028B-GD-08A	T10*28mm	Green	AC110V	BA9S	5±2mA	515 - 525	0.5lm	30K (h)	45°
LT1028B-GD-09A	T10*28mm	Green	AC220V	BA9S	3±2mA	515 - 525	0.3lm	30K (h)	45°
LT1028B-BD-01D	T10*28mm	Blue	DC 6V	BA9S	18±2mA	465 - 475	0.9lm	30K (h)	45°
LT1028B-BD-02D	T10*28mm	Blue	DC 12V	BA9S	18±2mA	465 - 475	1.0lm	30K (h)	45°
LT1028B-BD-03D	T10*28mm	Blue	DC 24V	BA9S	18±2mA	465 - 475	0.9lm	30K (h)	45°
LT1028B-BD-04D	T10*28mm	Blue	DC 28V	BA9S	19±2mA	465 - 475	1.0lm	30K (h)	45°
LT1028B-BD-05D	T10*28mm	Blue	DC 36V	BA9S	18±2mA	465 - 475	0.9lm	30K (h)	45°
LT1028B-BD-06D	T10*28mm	Blue	DC 48V	BA9S	16±2mA	465 - 475	0.7lm	30K (h)	45°
LT1028B-BD-07D	T10*28mm	Blue	DC 60V	BA9S	11±2mA	465 - 475	0.5lm	30K (h)	45°
LT1028B-BD-08A	T10*28mm	Blue	AC110V	BA9S	5±2mA	465 - 475	0.2lm	30K (h)	45°
LT1028B-BD-09A	T10*28mm	Blue	AC220V	BA9S	3±2mA	465 - 475	0.1lm	30K (h)	45°
LT1028B-AD-01D	T10*28mm	Amber	DC 6V	BA9S	19±2mA	590 - 600	0.6lm	30K (h)	45°
LT1028B-AD-02D	T10*28mm	Amber	DC 12V	BA9S	19±2mA	590 - 600	0.6lm	30K (h)	45°
LT1028B-AD-03D	T10*28mm	Amber	DC 24V	BA9S	18±2mA	590 - 600	0.6lm	30K (h)	45°
LT1028B-AD-04D	T10*28mm	Amber	DC 28V	BA9S	19±2mA	590 - 600	0.6lm	30K (h)	45°
LT1028B-AD-05D	T10*28mm	Amber	DC 36V	BA9S	17±2mA	590 - 600	0.5lm	30K (h)	45°
LT1028B-AD-06D	T10*28mm	Amber	DC 48V	BA9S	14±2mA	590 - 600	0.4lm	30K (h)	45°
LT1028B-AD-07D	T10*28mm	Amber	DC 60V	BA9S	11±2mA	590 - 600	0.3lm	30K (h)	45°
LT1028B-AD-08A	T10*28mm	Amber	AC110V	BA9S	6±2mA	590 - 600	0.2lm	30K (h)	45°
LT1028B-AD-09A	T10*28mm	Amber	AC220V	BA9S	4±2mA	590 - 600	0.1lm	30K (h)	45°
LT1028B-WD-01D	T10*28mm	White	DC 6V	BA9S	18±2mA	(K)5000-6000	2.4lm	30K (h)	45°
LT1028B-WD-02D	T10*28mm	White	DC 12V	BA9S	18±2mA	(K)5000-6000	2.4lm	30K (h)	45°
LT1028B-WD-03D	T10*28mm	White	DC 24V	BA9S	18±2mA	(K)5000-6000	2.4lm	30K (h)	45°
LT1028B-WD-04D	T10*28mm	White	DC 28V	BA9S	19±2mA	(K)5000-6000	2.4lm	30K (h)	45°
LT1028B-WD-05D	T10*28mm	White	DC 36V	BA9S	17±2mA	(K)5000-6000	2.3lm	30K (h)	45°
LT1028B-WD-06D	T10*28mm	White	DC 48V	BA9S	16±2mA	(K)5000-6000	2.1lm	30K (h)	45°
LT1028B-WD-07D	T10*28mm	White	DC 60V	BA9S	12±2mA	(K)5000-6000	1.5lm	30K (h)	45°
LT1028B-WD-08A	T10*28mm	White	AC110V	BA9S	6±2mA	(K)5000-6000	0.6lm	30K (h)	45°
LT1028B-WD-09A	T10*28mm	White	AC220V	BA9S	3±2mA	(K)5000-6000	0.2lm	30K (h)	45°

Design Current Will be a difference depends on the Vf value of LED bulb.

Copy Right